XLERATOR® HAND DRYER MOBILE HAND HYGIENE STATION

REMOVES 99.999% OF VIRUSES FROM THE AIRSTREAM¹





The World Health Organization And Centers
For Disease Control and Prevention List Proper
Hand Hygiene As Top Defense Against The
Spread Of Germs Like The Coronavirus.



Hand Sanitizer Dispenser Not Included

XLERATOR + HEPA = PROPER HAND HYGIENE

- Proper hand hygiene is washing and completely drying
- XLERATOR is proven to dry hands completely in as little as 8 seconds², per independent testing to global UL Environment PCR testing standards
- XLERATOR with HEPA Filtration removes 99.999% of viruses from the airstream

THE ULTIMATE SOLUTION FOR MOBILE HAND HYGIENE

STURDY & MOBILE

 Sturdy metal frame and base comes with handle and casters, allowing simple lean-and-roll mobility of entire unit

STANDARD PLUG-IN

Three-prong plug works off standard outlet

OPTIONAL HAND SANITIZER BRACKET

 Add your preferred hand sanitizer solution for even higher levels of hygiene

HAND DRYER BENEFITS

- ✓ HEPA Filtration System
- ✓ 95% cost savings vs. paper towels
- ✓ Industry-leading 7-year limited warranty
- ✓ Made In USA Certified®

ELIMINATE PAPER TOWEL HASSLES


- × Significant cost to purchase
- Currently in short supply
- X Inconvenience of ordering, shipping, restocking
- X Maintenance of germ-laden paper towel waste

XLERATOR® HAND DRYER MOBILE HAND HYGIENE STATION **PATENT PENDING**


MODEL: XL - SB - M - 110V

LIST PRICE: **\$2,500**











XL-SB + #40502 Brushed Stainless Steel XLERATOR with Recess Kit

FEATURES & BENEFITS

TESTED TO GUIDELINES

DRY TIME: 8 SECONDS²

ENERGY PER USE: 3.7 WH

- HEPA Filtration System Removes 99.999% of Viruses from the Airstream
- 50% Longer Life
- Industry Leading 7-Year Limited Warranty
- 95% Cost Savings Vs. Paper Towels
- **~** Made In USA Certified®
- A Hygienic Hand Drying Solution

INSTALLATION

Freestanding Plug in Unit

- Washable Pre-Filter
- Adjustable Sensor Range
 - Microban® Wall Guard

WFIGHT

XL-SB-M-110V: 142 Lbs

DRYER PERFORMANCE

ADJUSTABLE SOUND LEVEL: 65-75 dB ADJUSTABLE VELOCITY: 13,000-20,000 LFM

ADJUSTABLE FLOW RATE: 42-63 CFM

ADJUSTABLE HEAT RANGE: 72°F-135°F

VOLTS	AMPS	WATTS	NO HEAT AMPS	NO HEAT WATTS	HERTZ	
110-120V	11.3-12.2A	1240-1450W	4.3-4.5A	460-530W	50/60 Hz	c (UL) us

DRYER ELECTRICAL

VOLTS	AMPS	WATTS	NO HEAT AMPS	NO HEAT WATTS	HERTZ	
110-120V	11.3-12.2A	1240-1450W	4.3-4.5A	460-530W	50/60 Hz	c (UL) us

DIMENSIONS

ACTIVATION

Width: 23 3/4" (603.25mm) Base Depth: 23 3/4" (603.25 mm) **Top Depth:** 4 21/125" (105.87 mm) **Height:** 59 ¹/4" (1504.95 mm)

HAND DRYER CERTIFICATIONS

















UL LISTED COMPONENTS

Automatic Sensor Operated

The XLERATOR Mobile Unit is constructed with UL Listed components including: XLERATOR Hand Dryer, Wiring components and Cord with Plug.

Based on April 2020 testing performed by LMS Technologies. 2Dry time and energy use testing performed by SGS International on standard XLERATOR Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers



THROW IN THE T