

Short Form

[New Updated BIM/CAD Files Online](#)

Based on Excel Dryer XLERATOR Hand Dryer Model XL-SB:

- **Hand Dryer:** High Speed, energy efficient, electric hand dryer; surface mounted; entire dryer internally grounded.
- **Warranty Period:** 5 years; limited warranty.
- **Manufacturing** - MADE IN USA Certified, verify certification number.
- **Sound Level** – Operational sound level less than 80 dB.
- **Motor and Blower:** 5/8 HP, 20,000 RPM. Air flow rate: 19,000 linear feet per minute.
- **Heater:** 970 watts mounted inside blower housing to be vandal proof with Air Temperature of 135 degrees F measured at average hand position of 4 inches below air outlet.
- **Controls:** Completely sealed control board and optics, automatic operation, activated by infrared optical sensor.
- **Size:** 11-3/4" wide by 12-11/16" high by 6-11/16" deep.
- **Cover:** Stainless Steel [More Options Available Online](#)
- **Finish:** Brushed [More Finishes Available Online](#)
- **Green:** GreenSpec Listed, Qualifies for LEED Credits.

Options:

- **XLERATOReco[®]** - No heating element installed, 500W system.
- **Noise Reduction Nozzle:** 1.1 inch radius noise reduction nozzle lowers usage decibel level by 9 dB and reduces air deflection noise.
- **Recess Kit:** ADA compliant recess kit is fabricated of 22 GA 18-8 type 304 stainless steel with #4 satin finish with 16 GA18-8 type 304 stainless steel dryer mounting plate. All welded construction. 16-3/8 inches (416 mm) wide by 26 inches (660 mm) high by 3-3/8 inches (86 mm) deep.